

**TACKY SHEET**

**Patent number:** JP8333550  
**Publication date:** 1996-12-17  
**Inventor:** KUNIHIRO AKIRA; SUZUKI KENJI  
**Applicant:** NEW OJI PAPER CO LTD  
**Classification:**  
- international: C09J7/02; C09J7/02  
- european:  
**Application number:** JP19950142058 19950608  
**Priority number(s):** JP19950142058 19950608

**Report a data error here**

**Abstract of JP8333550**

**PURPOSE:** To obtain a tacky sheet capable of readily disintegrating without adversely being affected by a tacky agent and a film and doing not care even if mixed into a recycle process by using the film as the surface substrate. **CONSTITUTION:** In this tacky sheet, a surface substrate comprises a film having defibrability to an aqueous solution of an alkali and composed of a lactic acid- based polymer and a tacky agent constituting a tacky agent layer is a copolymer obtained by neutralizing a carboxylic acid-modified rosin-containing acrylic acid ester copolymer composed of a composition composed of (a) 5-40wt.% (poly)ethylene glycol (meth)acrylate monomer, (b) 5-40wt.% carboxylic acid- modified rosin ester monomer, (c) 30-60wt.% (meth)acrylic acid 4-18C alkylester monomer, (d) 5-20wt.% ethylenic unsaturated carboxylic acid-containing monomer and (e) 5-20wt.% monomer copolymerizable with these components (a), (b), (c) and (d) with an alkaline substance and having re-defibrability to water or an alkali aqueous solution.

Data supplied from the **esp@cenet** database - Worldwide